

Export Packaging

NEFAB ExPak

Type P

A lightweight, collapsible packaging system, designed to withstand the toughest transport conditions.

NEFAB ExPak is a collapsible export packaging system made of plywood and steel. This combination offers superior performance in terms of strength, weight, and volume utilisation. NEFAB ExPak has a proven track record worldwide in all industrial applications where valuable and sensitive goods require cost efficient protection and transportation.

NEFAB ExPak P consists of three sections – bottom, lid and foldable frame – and is delivered flat to save space and shipping costs. The integrated locking system of tabs and slots provides logical and efficient packing and unpacking. The container can be reused several times. Optional closing devices in spring steel and plastic facilitate reusing of the container.

A selection of standard sizes is available. Additionally, NEFAB ExPak P can easily be customised according to customer specifications. If required, the container can be supplemented with inner fittings and reinforcements modified to fit the product packed.



NEFAB ExPak box on a pallet.



A collapsed NEFAB ExPak P requires little space, e.g. cost savings for shipping and storage.



NEFAB ExPak P offers superb product protection – just what your products demand.



Lightweight, flexible sizes, easy to assemble.

NEFAB PACKAGING UK LTD

151 Silbury Boulevard, Milton Keynes,
MK9 1LH, United Kingdom
Tel: +44-(0)1908-424300, Fax: +44-(0)1908-424 301
Registered in London No. 4335687
uk@nefab.se • www.nefab.co.uk

NEFAB

Export Packaging

Specifications NEFAB ExPak Type P

General data

Material specifications

Sheet material specification	Birch plywood, eucalyptus plywood or OSB
Steel specification	Galvanized, P02G Z200
Sheet material thickness, lid	5, 6 or 8 mm
Sheet material thickness, base	5, 6 or 8 mm
Sheet material thickness, frame	5, 6 or 8 mm
Steel material thickness	0.4 and 0.8 mm

Marking

Locking alternatives	Plastic clip, spring latch
Pallet alternatives	Wooden runners, wooden four-way pallet, integrated four-way pallet in plywood/steel
Recommended min. size, internal	200x180x100 mm
Recommended max. size, internal	1600x1200x1000 mm
Other	Dangerous goods certification

Tech performance

Max. stacking load (excl. pallet)	3500 kg/m ²
Max. net weight of goods	Dependent on pallet configuration
Test report	On request

Sample size:

Box specifications: Internal dimension 1180 x 780 x 750 mm

(all specifications include pallet)	(ex: lid and base 8 mm)
Dimensions, external	1200x800x870 mm
Dimensions, internal	1180x780x750 mm
Volume, external	0.84 m ³
Volume, internal	0.69 m ³
Volume efficiency (internal/external)	82%
Tare weight	30 kg

Material specifications

Sheet material specification	Birch plywood
Steel specification	Galvanized, P02G Z200
Sheet material thickness, lid	6 or 8 mm
Sheet material thickness, base	6 or 8 mm
Sheet material thickness, frame	6 or 8 mm
Steel material thickness	0.4 and 0.8 mm

NEFAB PACKAGING UK LTD

151 Silbury Boulevard, Milton Keynes,
MK9 1LH, United Kingdom
Tel: +44-(0)1908-424300, Fax: +44-(0)1908-424 301
Registered in London No. 4335687
uk@nefab.se • www.nefab.co.uk