

Export Packaging

NEFAB ExPak

Type A

A lightweight, collapsible packaging system, designed to withstand the toughest transport conditions.

NEFAB ExPak is a collapsible export packaging system made of plywood and steel. This combination offers superior performance in terms of strength, weight, and volume utilisation. NEFAB ExPak has a proven track record worldwide in all industrial applications where valuable and sensitive goods require cost efficient protection and transportation.

NEFAB ExPak A consists of only one collapsible piece – bottom, lid and frame are attached to each other, simplifying handling and storage. The integrated locking system of tabs and slots provides logical and efficient packing and unpacking. The container can be reused several times. Optional closing devices in spring steel and plastic facilitate reusing of the container.

A selection of standard sizes is available. Additionally, NEFAB ExPak A can easily be customised according to customer specifications. If required, the container can be supplemented with inner fittings and reinforcements modified to fit the product packed.

- No loose parts
- Easy to assemble
- Requires little storage space



Collapsed box.



Unfold the frame.



Fold the bottom and seal the tongues.



Fold the lid and seal the tongues.

NEFAB PACKAGING UK LTD

151 Silbury Boulevard, Milton Keynes,
MK9 1LH, United Kingdom
Tel:+44-(0)1908-424300,Fax:+44-(0)1908-424 301
Registered in London No. 4335687
uk@nefab.se • www.nefab.co.uk

NEFAB

Export Packaging

Specifications NEFAB ExPak Type A

General data

Material specifications

Sheet material specification	Birch plywood, eucalyptus plywood or OSB
Steel specification	Galvanized, P02G Z200
Sheet material thickness, lid	5 or 6 mm
Sheet material thickness, base	5 or 6 mm
Sheet material thickness, frame	5 or 6 mm
Steel material thickness	0.4 and 0.8 mm

Marking

Locking alternatives	Plastic clip, spring latch
Recommended min. size, internal	180x180x90 mm
Recommended max. size, internal	600x600x400 mm
Other	Dangerous goods certification

Tech performance

Max. stacking load	3500 kg/m ²
Max. net weight of goods	Dependent on pallet configuration
Test report	On request

Sample size:

Box specifications: Internal dimension 300 x 300 x 250 mm

Dimensions, external	320x318x266 mm
Dimensions, internal	300x300x250 mm
Volume, external	27 dm ³
Volume, internal	23 dm ³
Volume efficiency (internal/external)	85%
Tare weight	2.7 kg

NEFAB PACKAGING UK LTD

151 Silbury Boulevard, Milton Keynes,
MK9 1LH, United Kingdom
Tel: +44-(0)1908-424300, Fax: +44-(0)1908-424 301
Registered in London No. 4335687
uk@nefab.se • www.nefab.co.uk

