

Export Packaging

NEFAB ExPak

Type S

A lightweight, collapsible packaging system, designed to withstand the toughest transport conditions.

NEFAB ExPak is a collapsible export packaging system made of plywood and steel. This combination offers superior performance in terms of strength, weight, and volume utilization. NEFAB ExPak has a proven track record worldwide in all industrial applications where valuable and sensitive goods require cost efficient protection and transportation.

NEFAB ExPak S consists of six sections – bottom, lid and four loose sides.

This design allows full access from all sides for loading and unloading, offering maximum flexibility in packing. The integrated locking system of tabs and slots provides logical and efficient packing and unpacking. The container can be reused several times. Optional closing devices in spring steel and plastic facilitate reusing of the container. A selection of standard sizes is available. Additionally, NEFAB ExPak-S can easily be customized according to customer specifications. If required, the container can be supplemented with inner fittings and reinforcements modified to fit the product packed.

- Flexible sizes
- Flexible thickness of plywood
- Suitable for large containers
- Can be assembled "around" the product



This piece can be used as lid or bottom



The four sides of NEFAB ExPak S



Bottom can be attached directly to a pallet



Nefab Standard tongue as locking device.

NEFAB PACKAGING UK LTD

151 Silbury Boulevard, Milton Keynes,
MK9 1LH, United Kingdom
Tel:+44-(0)1908-424300,Fax:+44-(0)1908-424 301
Registered in London No. 4335687
uk@nefab.se • www.nefab.co.uk

NEFAB

Export Packaging

Specifications NEFAB ExPak Type S

General data

Material specifications

Sheet material specification	Birch plywood, eucalyptus plywood or OSB
Steel specification	Galvanized, P02G Z200
Sheet material thickness, lid	1/4, 3/8 or 1/2 in
Sheet material thickness, base	1/4, 3/8 or 1/2 in
Sheet material thickness, frame	1/4, 3/8 or 1/2 in
Steel material thickness	1/32 in

Marking

Locking alternatives	Plastic clip, spring latch
Pallet alternatives	Wooden runners, wooden four-way pallet, integrated four-way pallet in plywood/steel
Recommended min. size, internal	16x8x4 in
Recommended max. size, internal	236x114x114 in
Other	Dangerous goods certification

Tech performance

Max. stacking load (excl. pallet)	717 lbs/sq.ft
Max. net weight of goods	Dependent on pallet configuration
Test report	On request

Sample size:

Box specifications:

(all specifications include pallet)	(ex: lid, base and sides 1/4 inch)
Dimensions, external (LxWxH)	48x27x25 in
Dimensions, internal (LxWxH)	47.1x26.1x19.5 in
Volume, external	19 cubic ft
Volume, internal	14 cubic ft
Volume efficiency (internal/external)	73%
Tare weight	77 lbs